

PowerWalker Modbus Card 2

Modbus Card 2

Simple way to achieve remote monitoring & controlling

Provides a pair of RJ-45 interface(RS232 and RS485)

Implements Modbus RTU protocol for communication with PCs



Item-No. 10120565


The PowerWalker Modbus Card is a communication accessory that provides a pair of RJ-45 interface for remote monitoring and controlling of UPSs. It converts standard RS232 signal to RS232 signal with specified address, which allows controlling many UPSs from one computer. You can setup a desired address with jumpers (range 0-255).

Product Features


For more details download see manual on our website

Supports following models:

- VFI 1000C, 2000C, 3000C, 6000C, 10000C LCD
- VFI 1000, 1500, 2000, 3000 LCD
- VFI 1000RM, 1500RM, 2000RM, 3000RM LCD
- VFI 6000R, 10000R LCD
- VFI 10000CP, 15000CP, 20000CP, 30000CP 3/3



Top view



Technical Details

Specifications

Protocol Support	Modbus RTU
Baud Rate	2400/4800/9600/19200bps
Parity	Even / Odd / None
Communication Port	RJ-45
Product Details	
Dimensions	85mm x 52mm x 26mm (D x W x H)
Colour	Black
Weight	34.7g
Model Code	Modbus Card

Environment

Temperature	0°C – 40°C
Humidity	0 - 95%

Logistic Data

Item Number	10120565
EAN Code	4260074975703
Warranty	24 Months

Version: EN 25/09/2014

We reserve the right for technical changes and mistakes