

EAP600

Dual Band Long Range Ceiling Mount Access Point

2.4GHz+5GHz 300Mbps+300Mbps 29dBm AP/WDS/Repeater



Package Contents

- 1* EAP600
- 1*Power Adapter
- 1*QIG
- 1*CD (User's Manual)
- 1*Ethernet Cable
- 1*T-Rail Mounting Kit
- 1*Ceiling/ Wall Mount screw kit
- 1*Mounting Bracket

EAP600 is a wireless-11n 600Mbps (300Mbps + 300Mbps) High Power Dual Band concurrent ceiling mount AP. It allows simultaneous operation of 2.4GHz and 5GHz wireless network. With media-optimized performance, you can enjoy internet surfing more smoothly and with less lag.

Maxima 29dBm high power transmission provides extended coverage in your environment. MSSID + VLAN make your data more secure and easy management. Standard PoE interoperable with 802.3af makes internet connection more flexible.

EAP600 designed with slim and white color outlook which will not violate your interior decoration. Multiple mounting types provide user friendly installation. EAP600 is the perfect choice in home and small business.

Software Features		
System Requirement		
System	Windows7, 98, ME, NT, XP, 2000. Mac OS X (10.4)	
Access method	Web Based (HTTP 1.0 / 1.1)	
Browser Compatibility	Microsoft IE 6.0 or above, Firefox 2.0 or above	
Status		
System Status	System Information	System Up Time, Device Name, Wireless MAC, LAN MAC, Country, Current Time, Firmware Version
	Current IP Setting	IP Address, Subnet Mask, Default Gateway, DHCP, DNS.
	Current Wireless Setting	Operation mode, Wireless Mode, Channel/Frequency, L2 Isolation, MSSID Setting
Client List	List current associated clients. Show only authorized and associated clients	
System Log	Displays a list of events triggered	

EAP600

Dual Band Long Range Ceiling Mount Access Point

2.4GHz+5GHz 300Mbps+300Mbps 29dBm AP/WDS/Repeater

Wireless Functional List		
Operation mode	AP	
	WDS	
	Repeater	
WDS detail	WDS AP	
	WDS bridge	
802.11 mode options	a/b/g/n	
Channel setting	Manual	
	Auto / Best Channel Selection	
Transfer rate setting	Auto and Manual	
Output Power Control	Select by dBm	
Power Saving	Wireless LAN power saving	
Multiple BSSID (Multi AP)	8 BSSID for 2.4Ghz , another 8BSSID for 5Ghz	
	Each BSSID should has its own WiFi & security settings	
WPS	Software only	
Security	WEP	WEP(64/128bit)
	WPA/ WPA2	TKIP / AES
	Hidden ESSID	
	MAC address filtering	MAC address filtering (WLAN, up to 50 field)
	802.1x Authenticator	MD5/ TLS/ TTLS, PEAP
LAN Settings	IP (check validity and DHCP server IP range) MAC	
VLAN	MSSID	VLAN tag on MSSID
	Management VLAN Ethernet Port VID	Only allow user with specified VID to access the device
	Tag/ Untag Option	Independent VLAN setting can be enable or disable
	Add VLAN tag	Any packet that enters the Device without a VLAN tag will have a VLAN tag inserted with a PVID (Ethernet Port VID)
SNMP	SNMP V1/V2C	- SNMP Active : Disabled / Enabled
	MIBI, MIBII	- SNMP Version : V1/V2c/ALL
	Private MIB	- Read Community - Set Community

EAP600

Dual Band Long Range Ceiling Mount Access Point

2.4GHz+5GHz 300Mbps+300Mbps 29dBm AP/WDS/Repeater

	<ul style="list-style-type: none"> - System Location - System Contract - Trap Active : Disabled / Enabled - Trap Manager IP
Administration	User Name (set as "admin", can be changed by user) Password (c set as "admin", can be changed by user)
Backup/ Restore Setting	Save Current Setting Restore Saved Setting Reset to Factory Default
QoS	WMM
Network Management System	NMS (EZ Controller) supported

Hardware Specifications

Memory/ Flash	64MB / 8MB		
Diameter * Height	161.5mm x 41.5mm		
Physical Interface	LAN: 1 x 10/100/1000 Gigabit Ethernet (802.3at PoE standard supported)		
	Reset		
	Power Jack		
LED Definition	Power x1	Orange	Booting: Blink at 1H Booting System Ready: On Firmware Upgrade: Blink at 4Hz System Off: Power Off
	WLAN x2	2.4G Blue 5G Green	Link: Solid Light / Active: Blinking (Receiving/ Transmitting data)
	LAN x1	Blue	Link: Solid Light / Active: Blinking (Receiving/ Transmitting data)
	WPS x1	Blue	WPS ready: On WPS running: Blink at 2Hz
Adapter	12V / 2A		

Wireless Specifications

Frequency Band	Radio I: 11b/g/n : 2.412~2.484 GHz Radio II: 11a/n :5.18 ~ 5.24 & 5.26 ~ 5.32 & 5.5 ~ 5.7 & 5.745 ~ 5.825 GHz
Modulation Technology	OFDM: BPSK, QPSK, 16-QAM, 64-QAM DBPSK, DQPSK, CCK

EAP600

Dual Band Long Range Ceiling Mount Access Point

2.4GHz+5GHz 300Mbps+300Mbps 29dBm AP/WDS/Repeater

Operating Channels	2.4G (11 for North America, 14 for Japan, 13 for Europe) 5G (TBD)depend on what region		
Wireless Setting	Operation Mode – AP / WDS / Repeater Wireless Mode – 11a/ 11b/ 11g /11n Channel Selection (Setting varies by Country) Channel Bandwidth (Auto, 20Mhz, 40Mhz) Transmission Rate – 2.4GHz: 11n only ,11b/g/n mix ,11b only ,11b/g, 11g only 5GHz: 11n only mode, 11a/n mix mode, 11a only mode		
Receive Sensitivity (Typical)	<p>802.11b</p> <p>-99dBm @ 1Mbps</p> <p>-93dBm @ 11Mbps</p> <p>802.11g</p> <p>-96dBm @ 6Mbps</p> <p>-82dBm @ 54Mbps</p> <p>802.11n (2.4GHz)</p> <p>-97dBm @ MCS0</p> <p>-78dBm @ MCS7</p> <p>-96dBm @ MCS8</p> <p>-76dBm @ MCS15</p>	<p>802.11a</p> <p>-90dBm @ 6Mbps</p> <p>-72dBm @ 54Mbps</p> <p>802.11n (5GHz)</p> <p>-89dBm @ MCS0</p> <p>-70dBm @ MCS7</p> <p>-89dBm @ MCS8</p> <p>-70dBm @ MCS15</p>	
Available transmit power (2 stream) (The Max. Power may be different depending on local regulations)	11b	1Mbps - 11Mbps	29
	11g	6Mbps - 9Mbps	29
		12Mbps - 18Mbps	28
		24Mbps - 36Mbps	24
		48Mbps - 54Mbps	23
	11n	MCS 0-1 / 8-9	29
		MCS 2-3 / 10-11	28
		MCS 4-5 / 12-13	24
		MCS 6-7 / 14-15	23
	11a	6Mbps - 9Mbps	26
		12Mbps - 18Mbps	25
		24Mbps - 36Mbps	24
		48Mbps - 54Mbps	23
11n	MCS 0-1 / 8-9	26	

EAP600

Dual Band Long Range Ceiling Mount Access Point

2.4GHz+5GHz 300Mbps+300Mbps 29dBm AP/WDS/Repeater

		MCS 2-3 / 10-11	25
		MCS 4-5 / 12-13	24
		MCS 6-7 / 14-15	23
Antenna	Internal 5 dBi MIMO ANT.		

Environment & Mechanical

Temperature Range	0 to 50° C - Operating, -20 to 60 ° C - Storage
Humidity (non-condensing)	90% or less – Operating, 90% or less - Storage

Certification

FCC	CE	IC
-----	----	----