


CODE: **AWT 8172430** v.1.1/X  
NAME: **TRANSFORMER TRZ 80/17/24/30**



**Tab.1**

Technical parameters of transformers							
CODE NAME	S	U	I	U1 or U2 or U3	I1 or I2 or I3	F	t
AWT8172430 TRZ 80/17/24/30	80VA	230V/AC	0,4A	17V or 24V or 30V	4,7A or 3,3A or 2,7A	T 630mA/250V	130°C

**USE:**


The transformers are destined for supplying devices requiring AC voltage U1 or U2 or U3.

**TECHNICAL DATA**

<b>Casing:</b>	PC/ABS in class UL 94 V-0, IP43
<b>Dimensions:</b>	Fig. 1 TRZ 80VA
<b>Net/ gross weight:</b>	1,70kg /1,78kg [+/-0,1kg] TRZ 80VA
<b>Installation:</b>	installation bus TH35/TS35 (DIN) or cheese screw x 4 (flat surface), with the holder AWO467 for TRZ80VA
<b>Supply voltage:</b>	230 V/AC (-15%+10%), 50Hz
<b>Current consumption I:</b>	tab.1. @~230 V / I1
<b>Output voltage U1 or U2 or U3:</b>	tab.1.
<b>Rated power S:</b>	tab.1.
<b>Rated output current I1 or I2 or I3:</b>	tab.1.
<b>Short-circuit protection F:</b>	fuse tab.1.
<b>Over-load protection t:</b>	fuse tab.1. / temperature limit fuse 130°C-non resetable
<b>Operating conditions:</b>	2nd environmental class, -10°C+ 40°C, Ta 40 B
<b>Declarations, warranty:</b>	CE, RoHS, 2 year from the production date
<b>Remarks:</b>	leads on connectors AWG 24-12 2,5mm <sup>2</sup> , screw 2,9 x 9,5 - 4pcs.

**Dimensions of transformers series: TRZ 80VA**

---



**Fig.1**